

4-CU.-FT. SPREADER

Ideal for treating sidewalks, driveways and small parking lots, the Sno-Way 4-Cu.-Ft. Receiver Spreader is the smart solution for small to midsize deicing applications.

The Sno-Way 4 delivers an all-new performance level to tailgate salt spreading. No other spreader in its class can match the simplicity of its design, ease of use or rugged construction. At an empty weight of just 95 pounds, the Sno-Way 4 is perfect for single operator handling. The integrated wheels and tapered Class III hitch make attaching the spreader a snap.



>> Easy portability for single person installation



SODIUM CHLORIDE
Rock Salt




CALCIUM CHLORIDE
Flake



BAGGED ICE MELTERS
Free Flowing

SNO-WAY 4-CU.-FT. SPREADERS REQUIRE A CLASS III RECEIVER HITCH FOR APPLICATION TO A VEHICLE

ALWAYS REMEMBER TO TAKE INTO CONSIDERATION SPREADER GROSS WEIGHT CAPACITIES WITH THE VEHICLE GVWR SPECIFICATIONS



Fully Encapsulated 12V Electric Motor

Sno-Way's 4 receiver spreader uses a 1/3 HP 12V DC electric motor that is separated from the hopper interior and isolated from the exterior of the spreader. This patent pending feature protects the motor from corrosive spread material and inclement weather. The motor components are also specially coated for added corrosion resistance.



Impact Resistant Nylon Roller Wheels

All Sno-Way's 4 receiver spreaders have integrated roller wheels for fast and easy portability. Forget bulky storage carts, Sno-Way provides you built-in mobility to move your spreader with ease. Unlike competitor's tailgate spreaders, Sno-Way's 4 can be easily mounted and removed from the truck by only one operator.



Standard Class III Tapered Receiver Hitch

All Sno-Way receiver spreader models include a standard Class III tapered hitch. The square tube has an angled face for easy insertion into the receiver on the truck and two adjustment holes to accommodate deeper locking points. All hitches include a 5/8" diameter bent arm hole pin and spring pin lock.



Enclosed Belt Reduction Drive Assembly

The belt reduction drive assembly transfers power from the electric motor to the spinner. Positioned in the center of the spreader and protected with a durable poly cover, the assembly is fully sealed from the elements and separated from corrosive spread material in the hopper. The belt drive tension is easy to adjust on this low maintenance spreader.

EASY SALT LOADING



EASY HITCH INSTALL

SPREADER FEATURES

- 1 - Fully Enclosed Belt Reduction Drive
- 2 - Fully Adjustable Flow Control Paddles
- 3 - Impact Resistant Nylon Roller Wheels
- 4 - Sealed Electric Motor
- 5 - Polyethylene Hopper Construction
- 6 - Automotive E-Coat Primer and Military Grade Powder Coat Finish
- 7 - Tapered Receiver Hitch (Class III)
- 8 - Vinyl Safety Labels
- 9 - Built-In Handles
- 10 - High Grade Polyethylene 12" Diameter Spinner
- 11 - External Stainless Steel Hardware
- 12 - Dual Flip-Up Hopper Lids
- 13 - UV Resistant Dual Wall Hopper



Exclusive Chunk Buster™ Salt Breakup System

More effective than an auger system, Sno-Way's exclusive Chunk Buster™ salt breakup system uses an inverted pyramid of bolts to easily crush salt clusters.

Move it.
SNO-WAY

Visit snoway.com for video, updates and so much more.